

This Page Is Inserted by IFW Operations
and is not a part of the Official Record

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

IMAGES ARE BEST AVAILABLE COPY.

**As rescanning documents *will not* correct images,
please do not report the images to the
Image Problem Mailbox.**

4/5/4

DIALOG(R)File 351:Derwent WPI

(c) 2002 Thomson Derwent. All rts. reserv.

012847676

WPI Acc No: 2000-019508/200002

XRPX Acc No: N00-015624

Electronic control apparatus of gas engine using natural gas as fuel
- has injection control unit which controls injection completion stage of
fuel injection valve of each air cylinder near TDC of suction stroke of
piston of each air cylinder

Patent Assignee: NIPPON JIDOSHA BUHIN SOGO (NIJI); NIPPONDENSO CO LTD
(NPDE)

Number of Countries: 001 Number of Patents: 001

Patent Family:

Patent No	Kind	Date	Applicat No	Kind	Date	Week
JP 11294222	A	19991026	JP 98104337	A	19980415	200002 B

Priority Applications (No Type Date): JP 98104337 A 19980415

Patent Details:

Patent No	Kind	Lan Pg	Main IPC	Filing Notes
JP 11294222	A		7 F02D-041/02	

Abstract (Basic): JP 11294222 A

NOVELTY - The control is provided with a ECU (33) which controls
fuel injection quantity and timing of fuel injection valve (19) of
each air cylinder. The control unit controls the injection completion
stage of fuel injection valve of each air cylinder within plus or minus
100 deg. of TDC of suction stroke of piston of each air cylinder.

DETAILED DESCRIPTION - The fuel injection valve which injects gaseous
fuel , is provided to a suction port (18) of each air cylinder.
Injected fuel is sucked into the combustion chamber before the injected
fuel spreads in a wide area within an inlet pipe (20). A fuel pressure
regulator (31) is provided for adjusting the injection pressure at 5 or
less kgf/cm2 within 3.5-4.5 kgf/cm2.

USE - For controlling gas engine.

ADVANTAGE - Reduces exhaust emission and raises convergency of air
fuel ratio at acceleration-deceleration time. DESCRIPTION OF DRAWING(S)
- The figure shows a part of control system of gas engine. (18) Suction
port; (19) Fuel injection valve; (20) Inlet pipe; (31) Fuel pressure
regulator; (33) ECU/injection control unit.

Dwg.1/7

Title Terms: ELECTRONIC; CONTROL; APPARATUS; GAS; ENGINE; NATURAL; GAS;
FUEL; INJECTION; CONTROL; UNIT; CONTROL; INJECTION; COMPLETE; STAGE; FUEL
; INJECTION; VALVE; AIR; CYLINDER; TDC; SUCTION; STROKE; PISTON; AIR;
CYLINDER

Derwent Class: Q52; Q53; X22

International Patent Class (Main): F02D-041/02

International Patent Class (Additional): F02M-021/02

File Segment: EPI; EngPI